

# ClubSpot 300 CT

### Technical specification

- Lamp: Philips MSD 250/2 or Osram HSD 250/80, BA 250/2 SE
- Lamp control: Automatic and remote on/off
- Ballast: Magnetic
- Protocol: USITT DMX-512,
- Control channels: 14/16
- Setting & Addressing: 4-digit LED display
- Pan/Tilt resolution: 8 or 16-bit
- Movement control: Tracking and vector
- Data in/out: Locking 3-pin XLR
- Colour wheel: 11 dichroic filters + open
- Rotating Gobo wheel :6 rotating, indexable, replaceable gobos + open
- Prism: 3-facet prism rotating on both directions at different speeds
- Dimmer/Shutter: Full range dimming and variable strobe effect,
- Zoom: Standard 15°, Optional 12° or 18° beam angle
- Focus: Motorized
- Pan: 530°
- Tilt: 280
- Operation modes: DMX, stand-alone, master/slave
- Programming: 3 free editable programs, each up to 99 steps



### Electrical specifications

- Wiring options: EU model: 208/230/240 V AC, 50/60Hz  
US model: 100/120/208/230/240 V AC, 50/60Hz
- Power consumption: 500 VA

### Mechanical specifications

- Mounting points : 4 pairs of ¼ turn lock, 2x Omega brackets
- Height: 498 mm (head in horizontal position)
- Width: 417 mm
- Depth: 398 mm
- EU-model: 20.5 kg, US-model: 24 kg