

ColorWash 700E AT

Technical specification

- Lamp: Phillips MSR Gold 700 FastFit
- Lamp control: Automatic and remote on/off
- Ballast: Electronic
- Protocol: USITT DMX-512,
- Setting & Addressing: ROBE Navigation System (RNS)
- Pan/Tilt resolution: 16-bit
- Movement control: Tracking and vector
- Ethernet port: Art-Net protocol, ready for ACN
- Data in/out: Locking 3-pin & 5-pin XLR
- Cyan: 0-100%, Magenta: 0-100%, Yellow: 0-100%, CTO: 0-100%
- Colour wheel: 8 replaceable "SLOT&LOCK" dichroic filters + open
- Effect wheel: rotating, indexable beam shaper
- Dimmer/Shutter: Full range dimming and variable strobe effect, Electronic strobing „ZAP”
- Linear zoom 8 - 50°
- Pan: 530°
- Tilt: 280°
- Fixation option: Pan/Tilt-lock mechanism



Electrical specifications

- Wiring options: 100/120/208/230/250 V AC

Mechanical specifications

- Mounting points : 4 pairs of ¼ turn lock, 2x Omega brackets
- Height: 597 mm (head in horizontal position)
- Width: 514 mm
- Depth: 499 mm