

X23

2-
3-



www.altoproaudio.com

- -



ON:
OFF:

WARNING:

CAUTION:

(Fuse)

,
LTO AUDIO. LTO,
— , ...
!
LTO
, ,
(DSP) , ,
7 . ,
, ,
, ,
, !
LTO — , «
».
- ,
, LTO , LTO,
, — ,

LTO AUDIO

1.			4
2.			4
3.			4
	3.1			
		a.		
		b.		
	3.2			
		a.		
		b.		
4.		&	7
	4.1			
	4.2			
	4.3.			
5.			8
	5.1	23		
		2-		
	5.2	23		
		3-		
6.			10

1.


LTO 23 – U, 23, () 3-
 () - ()
 CD Horn Equalization ()
 23 -

2.

- 1 U
- / XLR, ¼- / TRS
- , 24 /
- Mute
- 115
- ISO9001

3.

3.1




	24 – 2- () / 3- ()	()
1.	2-	3-
2.	1,	
3.	1,	
4.	1,	()
5.	1,	()
6.	1,	()
7.	1,	()
8.	1,	()
9.	1,	-

10.	2,	()
11.	2,	
12.	2,	
13.	2,	
14.	2,	-
15.	2,	
16.	2,	
17.	2,	()

b.

- POWER (1)
- CLIP (3) 1 11 2)
- MUTE (5, 9) 1 13, 17 2)

3.2 :



	23 - 2-	() / 3-	()
	2-		3-
18.			
19.			
20.	1,		
21.	1,		
22.	1, -	()	
23.	1,	()	
24.	1, -	()	
25.	1,	()	
26.	1, -		-
27.	2,	()	
28.	/		
29.	2,	()	
30.	2, -		
31.	2, -		-

b.

(22 23)



100-120

220-240

3

(

).

1800

(20 22, 24

1, 25, 28 30

2)

(« »).

• CD Boost
1 27

2)

(21

+3 3,5

6 / 22,5

«CD BOOST»,

(

).

(23

1 29

2)

180°.

(26)

(/ / /).

4-

(/ /).

3-

4. & :

4.1

X34

34,

[POWER]
/

4.2

LTO 34
XLR 1/4" TRS Jack.

a.

1/4" TRS (Tip-Ring-Sleeve) XLR

-

1/4" TRS



1/4" TRS



1/4" TRS

-

XLR



XLR







XLR

b.

XLR, 1/4" TRS,

-






4.3.

5.

5.1. 23 2-

23 2-


	Mode	INPUT 1	INPUT 2.
1.			
2.			
3.	-	LOW OUT 1	- , - LOW OUT 2
4.	-	MID OUT 1	- , - MID OUT 2
5.	-	HIGH OUT 1	- , - HIGH OUT 2



5.2. 23 3-

23 3-

1. Mode
2. INPUT 1.
3. LOW OUT 2
4. HIGH OUT 2
5. HIGH OUT 1



INPUT 2.
LOW OUT 1 MID OUT 1.

- INPUT 1
- LOW Gain 1
- XOVER FREQ 1
- HIGH Gain 1
- INPUT 2
- LOW Gain 2
- XOVER FREQ 2
- HIGH Gain

6.

```

:
-
-
( 0 )
( 0 )
( 0 )
/
:
INPUT LEVEL ( )
OUTPUT LEVEL ( )
CD Boost ( )
MUTE ( )
PHASE ( )
:
3- IEC,
-
115 230 , 50/60
10
:
483 194,5 44
2,5
```