Gitarrenkabel Top Performance

Kabel klingen. In kaum einer anderen Anwendung wird diese Erkenntnis so deutlich wie im Gitarrenkabel-Einsatz zwischen hochohmigen Pickups und den Eingängen von Röhrenverstärkern.
Das CORDIAL®-Top-Performance Gitarrenkabel reagiert darauf mit einem kapazitätsoptimierten Aufbau und Werten von unter 70pF/m. Die zusätzliche Ummantelung aus Conductiv Plastic bewirkt eine hohe Nebengeräusch-Dämpfung.
Dieses High End-Kabel verleiht elektrischen Saiteninstrumenten nach Aussagen vieler Studiomusiker Schub und Transparenz, die sie vorher nicht für möglich gehalten hätten.

Guitar Cable Top Performance

Cables do sound. No other application proves this more than the use of cables as connection between high ohm pick ups and the input of valve guitar amplifiers.
The CORDIAL® Top Performance guitar cable responds to this with an optimised capacitance value of less than 70pF/m. The additional coating with conductive plastic results in a significant noise attenuation.
According to the statements of studio musicians this high end cable gives many electric string instruments boost and transparency that they would never have expected.



CGK-Serie
1 = Mantel
2 = Leiter
3 = Abschirmung
4 = Leiterisolation
5 = Conductive plastic

Bestell-Nr.	Part No.	CGK 122
Mechanische Daten	**Mechanical data**	
Leiterquerschnitt	Conductor area	0,22 mm²
Leiteraufbau	Composition of conductor	7 x 0,20 mm Cu blank / Bare copper
Leiterisolation	Conductor insulation	foam-skin PP
Schirm	Screen	Umseilung aus blanken Cu-Drähten + 2x Schirm aus leitendem Kunststoff Spiral wound copper wire screen + 2x Conductive plastic
Gesamtmantel	Overall jacket	PVC, Farbe / Colour: ■ SW
Gesamtdurchmesser	Overall diameter	7,20±0,25 mm
Gewicht	Weight	ca. 57 g/m
Betriebstemperatur bewegt unbewegt	Working temperature mobile fixed	(– 5°C) – (+70°C) (–20°C) – (+70°C)
Elektrische Daten	**Electrical data**	
Leiterwiderstand	Conductor resistance	90 Ohm/km
Kapazität (Leiter/Leiter)	Capacity (Cond./Cond.)	70 pF/m

Technische Änderungen vorbehalten
Technical alternations reserved