The Soundraiser.







HDVD 800

Pure audio in perfection. Get the most from your high-end headphones - with the HDVD digital headphone amplifier from Sennheiser. Fully symmetrical signal processing and extremely low harmonic distortion allow for pure, unbeatable listening enjoyment.

- Symmetrical signal processing with exact signal transmission over the entire frequency spectrum and very low harmonic distortion
- Operation with up to four dynamic, high-impedance headphones
- High transmission bandwidth and signal fidelity thanks to short signal paths
- Symmetrical XLR-4 sockets and highquality 6.35 mm jack sockets for connecting headphones
- High level of flexibility thanks to wide range of connection options

192 kHz (AES3-compatible)

Technical Data

HDVD 800

EAN	4044155079067
UPC	615104229716
Article. No.	505590

UPC	615104229716	
Article. No.	505590	
Power supply Input voltage:	100240 V AC / 5060 Hz	

Power consumption: < 30 VA Max. resolution: 24 bit **Audio inputs** Digital AES/EBU (XLR-3) Analogue input (XLR-3) 192 kHz (AES3-compatible) Max. sampling frequency: Max. resolution: 24 bit Max. input voltage

14 dBV (symmetrical, eff):

USB (USB-B) USB standard: 10 kOhm Input impedance: USB 2.0 / USB 3.0 USB audio class: USB Audio 2.0 Analogue input (RCA) Max. input voltage (eff): 20 dBV

Input impedance: 10 k0hm Frequency response: 0.3 Hz to 100 kHz (-3 dB) Total harmonic distortion: < 0.001 % Digital SPDIF (RCA)

Max. sampling frequency: 192 kHz (AES3-compatible) Weight of product: 2.2 kg Max. resolution: 24 bit Dimension of product

(W x H x D): approx. 224 x 44 x 306 mm

Packaging	
Packaging type	Closed carton box, e-flute
Content of Delivery	amplifier, CD with user manual plus driver software for Windows, Quick Guide and Safety Guide
Dimensions of product packaging (W x D x H)	approx. 390 mm x 272 mm x 80 mm
Weight of product and packaging	approx. 2.85 kg
Dimension of Master carton (W x D x H)	approx. 500 x 320 x 280 mm
Weight of Master carton	approx. 10 kg
Units per Master carton	3

Audio data

Digital SPDIF (TosLink)

Max. sampling frequency: